


**29-UC050-SAAB  
SAAB 9-3 and 9-5 2006>  
STEERING CONTROL INTERFACE**



14 Pin connector on interface box as seen from wire entry side.



- 2 Green = Can High
- 3 Orange = Illumination output
- 4 Brown = Steering control output
- 5 Red = Ignition output
- 7 Yellow = 12V+ input
- 8 Black = Steering control output
- 9 White = Can Low
- 10 Blue = Reverse output
- 11 Grey = Speed pulse output
- 12 Purple = Steering control output
- 14 Black = Ground input

Use this interface along with a head unit specific patch lead, pins 4, 8 and 12 terminate at a 4 Pin connector, this is where you will need to connect the head unit patch lead.

When connected the LANbus interface will automatically recognise the vehicle. The green LED on the interface will repeatedly flash once followed by a pause. If the LED is solid green you will need to follow the instructions at the bottom “to reprogram the interface for another head unit”.

**You will need to set the interface to the make of head unit you are fitting.**

The amount of flashes between pauses corresponds to the make of head unit, see the table over-leaf for the number of flashes and which make it corresponds to.

While the LED is flashing green, press the Vol +/- buttons on the cars steering wheel to change the amount of flashes between pauses, Vol + will increase the amount of flashes, Vol- will decrease the amount of flashes.

When you have the correct amount of flashes, press seek+ to confirm and the LED will go to a solid green light.


Number of flashes	Make of head unit
1	Clarion (Default)
2	Kenwood
3	JVC
4	Alpine
6	Pioneer (Set jumper)
7	Sony

**To reprogram the interface for another head unit make**


- Disconnect the interface from the 14 Pin connector.
- Push the reset button in and keep it pushed in.
- Reconnect the interface to the 14 Pin connector
- The LED will flash green then go off.
- Release the reset button.
- The LED will flash red then green.
- Use Vol+/- to set the amount of flashes
- Confirm selection with Seek +

## Setting the jumpers

There are a series of jumper pins on the interface board. These may need to be changed depending on the head unit you are fitting or the type of outputs you require.



To set the jumpers, the jumper clip will need to be placed over the corresponding pins. See the above picture and diagram to the right. In the example picture above it is set for Pioneer, Ground handbrake output, positive reverse output and CANbus handling.



It can be possible to retain the use of the original telephone buttons, however by making this connection for the telephone command, the ignition and speedpulse outputs from the interface will be lost. A new ignition power supply to the head unit will need to be provided.

The LANbus connection at the back of the radio will need to be cut and extended to the steering column. Cut the green wire in pin 2 and extend to the steering column. A connection to one of the green LANbus wires needs to be made here.

There are a few LANbus wires here carrying signals on different parts of the network, you may have to try a few different wires to find the correct one carrying the telephone commands.

*We recommend this is done by an experience car audio technician.*




## To reset the interface (if installing into another vehicle)


With the interface powered, press and hold the reset button. When the LED goes off, release the reset button. The LED will go to green and the reset is complete.

29-UCCAB-001	Alpine
29-UCCAB-003	Clarion/JVC
29-UCCAB-005	Kenwood
29-UCCAB-007	Pioneer/Sony
29-UCCAB-000	Chinese/Learning


All diagrams are seen from the wire entry side of the connector.




The connector for the patch lead from the UNICAN interface.




29-UCCAB-001 Alpine  
 Base to black  
 Ring to brown \* 13.7K resistor inline  
 Tip to purple




29-UCCAB-003 Clarion/JVC  
 Base to black  
 Tip to brown \* and single wire



29-UCCAB-005 Kenwood  
 Single wire to brown and din



29-UCCAB-007 Pioneer  
 Tip to purple  
 Ring to brown  
 Base to black



29-UCCAB-000 Chinese/Learning  
 2x single wire connections  
 Connect to the learning input wires on the head unit



Please note, we have not mentioned black, white and red colours for the patch lead wiring as the pinning of red and white to tip and ring can vary depending on the manufacturer of these leads.

These patch leads are to be used with the 29-UC-range of CANbus steering control interfaces.

In addition to using the correct patch lead, the interface will need to be set to the corresponding brand of head unit. Follow the instructions supplied with the interface for this setup.