

This antenna adapter is suitable for various Nissan vehicles with an original amplified FM/AM antenna.

InCarTec

#### Compatible with various Nissan vehicle models:

370Z (08>), Cube (10), Elgrand (07-10), GT-R (07 >), Juke (10-19), Leaf (11-17), Maxima (09-14), Micra (07 >), Murano (08-14), Navara D40 (05-16), Navara NP300 (16-19), Note (06-18), NV200 (10 >), Pathfinder (05-13), Patrol Y62 (11 >), Pulsar J11 (14-18), Qashqai (07-17), Rogue (08-11), Serena (05-10), Tiida (04-11) and X-Trail (07-17).

### PLEASE NOTE: Not suitable for DAB aerials

## Installation

1. Connect the ISO connector to the original AM/ FM antenna connection in the car.

- 2. Connect the DIN aerial connection to the back of the after market radio.
- 3. Connect the bullet connector (on the blue wire) to the blue antenna turn on wire, or the blue/white

remote turn on wire coming from the new aftermarket radio harness

Some aftermarket ISO leads have a bullet connection for this purpose (Figure A)

The wiring that came with the radio may have a bullet connection it can be connected to (Figure B)



If neither of these are available then you will need to cut off the supplied bullet terminal and splice the wire into the Blue or Blue/white on the radio harness. Use a T Tap style connector or solder the wires together.

# **Trouble Shooting**

### I have poor FM reception

Check that the adapter is securely connected to the original ISO connection in the car, they can come apart if they get caught when installing the new radio into the dashboard.

### l have no sound

Some cars also need the remote turn on wire for waking up an original amplifier. If there is no sound then make sure that the remote on is connected through to the car as well as to the bullet connection.

PLEASE NOTE: If you have needed to make your own connection for the remote turn on wire then make sure that the connection is secure and that 12v is output when the radio is on.