

r.LiNK-Interface

27-314

(RL-LR15-TF)

**Rear-view camera-input
and
video-in-motion
for Land Rover
touch-screen navigation system
version 4 from model 2015**

Only for vehicles WITHOUT factory rear-view camera

Contents

1. Prior to installation

- 1.1. Delivery contents
- 1.2. Check compatibility of vehicle and accessories
- 1.3. Setting the Dip-switches of the CAN-Box TV-400/500
- 1.4. Pin-assignments

2. Connection schema

3. Installation

- 3.1. Interconnecting CAN-box, harness and factory navigation monitor
- 3.2. Connection to rear-view camera

4. Activation of the video-in-motion function

5. Specifications

Legal Information

By law, watching moving pictures while driving is prohibited, the driver must not be distracted. We do not accept any liability for material damage or personal injury resulting, directly or indirectly, from installation or operation of this product. This product should only be used while standing or to display fixed menus or rear-view-camera video when the vehicle is moving, for example the MP3 menu for DVD upgrades.

Changes/updates of the vehicle's software can cause malfunctions of the interface.

1. Prior to installation

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources.

1.1. Delivery contents

Take down the SW-version and HW-version of the interface boxes, and store this manual for support purposes.

CAN-box TV-500
HW ____ SW ____



1.2. Check compatibility of vehicle and accessories


Requirements

Vehicle Land Rover vehicles **from year 2015**

Navigation Touch-screen navigation version 4



Version I



Version II



Version III



Version IV

Limitations

After-market rear-view camera Only compatible with NTSC-cameras.

1.3. Setting the dip switches of the CAN-box TV-500

Vehicle/ navigation	Dip 1	Dip 2	Dip 3	Dip 4	Dip 5	Dip 6
Video-in-motion permanent	ON	ON	OFF	OFF	ON	ON
Video-in-motion selective*	OFF	ON	OFF	OFF	ON	ON

* With dip1 to OFF the included green cable is used to activate the video-in-motion function

Note: Dip switch functions of the TV-500

Dip 1 – activation TV-free

Dip 2 – rear-view camera existing

Dip 3 – no function

Dip 4 – no function

Dip 5 – CAN-bus termination resistor on the vehicle side


Dip 6 – CAN-bus termination resistor on the head-unit side

Setting dip 2 to ON codes the factory rear-view camera input which is located on the blue double Fakra male connector of the head unit. When reverse gear is engaged, the navigation will automatically switch to this input.

1.4. Pin-assignments

Pin assignment quadlock connector

Function	Pin-No.
CAN-HIGH	Pin 3 (chamber B)
CAN-LOW	Pin 9 (chamber B)
+12V permanent	Pin 13
Ground	Pin 11




No liability for vehicle wire colors and pin definition! Possible changes by the vehicle manufacturer. The given information must be verified by the installer.

Pin-assignment of the CAN-Box TV-500 (Molex 8pin)

Cable colour	Pin-No.	Assignment
Yellow	Pin 4	CAN-HIGH – connection to the head-unit
Blue	Pin 3	CAN-LOW – connection to the head-unit
Yellow/Black	Pin 8	CAN-HIGH – connection to the vehicle
Blue/Black	Pin 7	CAN-LOW – connection to the vehicle
Red	Pin 1	+12V permanent
Black	Pin 5	Ground
Green	Pin 6	Activation of the video-in-motion function (+12V = TV-free activated)
White	Pin 2	No function

2. Connection schematic




3. Installation

Switch off ignition and disconnect the vehicle's battery! If according to factory rules disconnecting the battery has to be avoided, it is usually sufficient to put the vehicle in sleep-mode. In case the sleep-mode does not show success, disconnect the battery with a resistor lead.


Place of installation is on rear of the head unit.

3.1. Interconnecting CAN-Box, harness and factory head unit



- ① Connect female 8pin Molex connector of harness TV-LR05 to male 8pin Molex connector of CAN-box TV-500.
- ② Transfer Quadlock connector of vehicle harness from rear of the head unit into male Quadlock connector of harness TV-LR05.
- ③ Plug female Quadlock connector of harness TV-LR05 into male Quadlocksocket on the rear of the head unit.

3.2. Connections to rear-view camera



- ① If existing, disconnect the original blue double Fakra socket from the Head Unit and connect it to the double Fakra male plug of adapter CAB-LR15-R.
- ② Connect the double Fakra socket of adapter CAB-LR15-R to the double blue Fakra-connector on the rear of the head unit.
- ③ Connect the video RCA of the rear-view camera to the female RCA connector of adapter CAB-LR15-R.

Note: Only compatible with NTSC-cameras.

4. Activation of the video-in-motion function

The video-in-motion can be activated and deactivated by Dip 1 or alternatively by the included loose green cable in connection with a switch (not included in delivery).

Video-in-motion permanent

With dip1 to ON the video-in-motion function is activated permanently without disturbing the navigation performance.

Video-in-motion selective

With dip1 to OFF the included green cable is used to activate the video-in-motion function.

Connect a switch to the green cable and connect the green cable to +12V ACC.

- +12V = TV-Free is activated
- 0V = TV-Free is not activated

Note: The loose white cable is not required and must be isolated.

5. Specifications

Operation voltage	10.5 – 14.8V
Stand-by power drain	<2mA
Operation power drain	~60mA
Power consumption	~0,08W
Temperature range	-30°C to +80°C
Weight	44g
Measurements (box only)	W x H x D 70 x 20 x 47 mm/ 76 x 27 x 54 mm